

# Online Research @ Cardiff

This is an Open Access document downloaded from ORCA, Cardiff University's institutional repository: <https://orca.cardiff.ac.uk/id/eprint/108148/>

This is the author's version of a work that was submitted to / accepted for publication.

Citation for final published version:

Khaki, M., Forootan, Ehsan ORCID: <https://orcid.org/0000-0003-3055-041X>, Kuhn, M., Awange, J., Papa, F. and Shum, C.K. 2018. A study of Bangladesh's sub-surface water storages using satellite products and data assimilation scheme. Science of the Total Environment 625 , pp. 963-977. 10.1016/j.scitotenv.2017.12.289 file

Publishers page: <http://dx.doi.org/10.1016/j.scitotenv.2017.12.289>  
<<http://dx.doi.org/10.1016/j.scitotenv.2017.12.289>>

Please note:

Changes made as a result of publishing processes such as copy-editing, formatting and page numbers may not be reflected in this version. For the definitive version of this publication, please refer to the published source. You are advised to consult the publisher's version if you wish to cite this paper.

This version is being made available in accordance with publisher policies.

See

<http://orca.cf.ac.uk/policies.html> for usage policies. Copyright and moral rights for publications made available in ORCA are retained by the copyright holders.



# A Study of Bangladesh's Sub-surface Water Storages Using Satellite Products and Data Assimilation Scheme

M. Khaki<sup>a,1</sup>, E. Forootan<sup>b</sup>, M. Kuhn<sup>a</sup>, J. Awange<sup>a</sup>, F. Papa<sup>c,d</sup>, C. K. Shum<sup>e,f</sup>

<sup>a</sup>*Department of Spatial Sciences, Curtin University, Perth, Australia.*

<sup>b</sup>*School of Earth and Ocean Sciences, Cardiff University, Cardiff, UK.*

<sup>c</sup>*LEGOS, Universit de Toulouse, IRD, CNES, CNRS, UPS, Toulouse 31400, France.*

<sup>d</sup>*Indo-French Cell for Water Sciences (IFCWS), IRD-IISc-NIO-IITM Joint International Laboratory, Bangalore 560012, India.*

<sup>e</sup>*Division of Geodetic Science, School of Earth Sciences, The Ohio State University, Columbus, OH, USA.*

<sup>f</sup>*Institute of Geodesy and Geophysics, Chinese Academy of Sciences, Wuhan 430077, China.*

---

## Abstract

1 Climate change can significantly influence terrestrial water changes around the world particu-  
2 larly in places that have been proven to be more vulnerable such as Bangladesh. Its impacts,  
3 together with those of excessive human water use, in the past few decades have changed the  
4 country's water availability structure. In this study, we use multi-mission remotely sensed mea-  
5 surements along with a hydrological model to separately analyze groundwater and soil moisture  
6 variations for the period 2003–2013, and their interactions with rainfall in Bangladesh. To im-  
7 prove the model's estimates of water storages, terrestrial water storage (TWS) data obtained  
8 from the Gravity Recovery And Climate Experiment (GRACE) satellite mission are assimilated  
9 into the World-Wide Water Resources Assessment (W3RA) model using the ensemble-based  
10 sequential technique of the Square Root Analysis (SQRA) filter. We investigate the capability  
11 of the data assimilation approach for using a non-regional hydrological model for studying water  
12 storage changes. Based on these estimates, we investigate connections between the model de-  
13 rived sub-surface water storage changes and remotely sensed precipitations, as well as altimetry-  
14 derived river level variations in the area by applying the empirical mode decomposition (EMD)  
15 method. A larger correlation is found between river level heights and rainfalls (78% on average)  
16 in comparison to groundwater storage variations and rainfalls (57% on average). The results  
17 indicate a significant decline in groundwater storage ( $\sim 32\%$  reduction) for Bangladesh between  
18 2003 and 2013, which is equivalent to an average rate of  $8.73 \pm 2.45$  mm/year.

**Keywords:** Bangladesh, Groundwater storage, Data assimilation, Hydrological modelling, GRACE

---

---

*Email address:* Mehdi.Khaki@postgrad.curtin.edu.au (M. Khaki)

<sup>1</sup>Contact details: Western Australian Centre for Geodesy and The Institute for Geoscience Research, Curtin University, Perth, Australia, Email: Mehdi.Khaki@postgrad.curtin.edu.au, Tel: 0061410620379

## 1. Introduction

South Asia, and in particular Bangladesh, is amongst the most water vulnerable regions of the world exhibiting an increase in droughts and floods due to climate change (McCarthy et al., 2001). Groundwater is the main source of drinking and irrigation water (almost 90%) in the country (Islam et al., 2013). Any considerable change in climate will, therefore, affect Bangladesh's available water, which is stored in different forms including aquifers, soils, surface waters as rivers, lakes, man-made reservoirs, wetlands and seasonally inundated areas (Papa et al., 2015). Understanding the interaction between precipitation (mainly provided during the Monsoon season) and water storage changes is important to relate climate variability to hydrology. An in-depth understanding of this interaction can be more difficult in Bangladesh due to the changing behavior of monsoonal precipitation (Wang and Ding, 2006) as well as the lack of knowledge on their influence on the hydrology of the region (Shahid, 2010; Rafiuddin et al., 2010).

Groundwater accessibility has made Bangladesh an agro-based country with the main product being rice, making it one of the world's largest rice producer (Abdullah Aziz et al., 2015). The excessive groundwater usage during the last two decades has resulted in serious problems of both rapid falling of groundwater levels and the deterioration of its quality (Qureshi et al., 2015). Groundwater depletion has been reported by Shamsudduha et al. (2009) between 1985 and 2005 within different regions in Bangladesh such as north-central, northwestern, and southwestern parts of the country. This has also been shown by Shamsudduha et al. (2012) for the period of 2003 to 2007. Moreover, Sengupta et al. (2013) reported that groundwater in 63 (out of 64) districts of Bangladesh are seriously contaminated with arsenic, which is partly attributed to its depletion. A number of studies attribute the drop in groundwater level since 1972 to the rainfall decrease and increase in human water usage (see, e.g., Mainuddin, 2002; Ahmed, 2006; McBean et al., 2011; Dey et al., 2011; Adhikary et al., 2013). The Groundwater Monitoring Survey Report of Bangladesh Agricultural Development Corporation (BADC) and Institute of Water Modeling (IWM) showed a three-meter drop of groundwater levels in Dhaka (Sumon and Abul Kalam, 2014). Knappett et al. (2016) claimed that an excess extraction caused the groundwater level to decline more than one meter near the Buriganga River, which passes in the southwest outskirts of Dhaka resulting in insufficient resources available for the rapidly growing population.

Soil water storage variation is another important factor that worsens the situation and affects

51 agriculture. Furthermore, a considerable amount of surface water from rainfall is consumed by  
 52 human and thus is not able to recharge the groundwater (e.g., [Kanoua and Merkel, 2015](#); [Qureshi](#)  
 53 [et al., 2015](#); [Alimuzzaman, 2017](#)), which can aggravate the conditions mentioned above. Apart  
 54 from efforts by these studies, a comprehensive study is missing to account for both groundwater  
 55 and soil moisture variations and their connections to climate variability and change over the  
 56 entire Bangladesh.

57 In this regard, hydrological models are important tools for simulating and predicting sub-  
 58 surface water storages with high spatio-temporal resolutions (e.g., [Wooldridge and Kalma,](#)  
 59 [2001](#); [Döll et al., 2003](#); [van Dijk et al., 2013](#)). However, imperfect modeling of complex water  
 60 cycle processes, data deficiencies on both temporal and spatial resolutions (e.g., limited ground-  
 61 based observations), and uncertainties of (unknown) empirical model parameters, inputs and  
 62 forcing data cause some degrees of deficiencies in them ([Vrugt et al., 2013](#); [van Dijk et al.,](#)  
 63 [2011, 2014](#)). These limitations are addressed through data assimilation, which is a technique  
 64 that incorporates additional observations into a dynamic model to improve its state estimations  
 65 ([Bertino et al., 2003](#); [Hoteit et al., 2012](#)). The technique has been widely applied and validated  
 66 in the fields of oceanography, climate, and hydrological science ([Garner et al., 1999](#); [Elbern](#)  
 67 [and Schmidt, 2001](#); [Bennett, 2002](#); [Moradkhani et al., 2005](#); [van Dijk et al., 2014](#); [Reager](#)  
 68 [et al., 2015](#)). Several studies indicate that terrestrial water storage (TWS) derived from the  
 69 Gravity Recovery And Climate Experiment (GRACE) can play a significant role in better  
 70 understanding surface and sub-surface processes related to water redistribution within the Earth  
 71 system (e.g., [Huntington, 2006](#); [Chen et al., 2007](#); [Kusche et al., 2012](#); [Forootan et al., 2014](#);  
 72 [van Dijk et al., 2014](#)). In particular, [Shamsudduha et al. \(2012\)](#) showed a high capability of  
 73 GRACE measurements for studying water storage variations in the Bengal Basin. A growing  
 74 number of studies have also assimilated GRACE TWS in order to constrain the mass balance of  
 75 hydrological models (e.g., [Zaitchik et al., 2008](#); [Thomas et al., 2014](#); [van Dijk et al., 2014](#); [Eicker](#)  
 76 [et al., 2014](#); [Tangdamrongsub et al., 2015](#); [Reager et al., 2015](#); [Khaki et al., 2017c](#); [Schumacher](#)  
 77 [et al., 2017](#)).

78 The present study aims at assimilating GRACE TWS into the World-Wide Water Resources  
 79 Assessment (W3RA) hydrological model ([van Dijk, 2010](#)) to analyze groundwater and soil mois-  
 80 ture changes within Bangladesh. While the main focus is on groundwater and soil moisture,  
 81 surface water as an important water source in Bangladesh is also studied since some surface  
 82 water sources (e.g., lakes and rivers, except major ones) are not modeled in W3RA. Moreover,

since GRACE TWS reflects the summation of all water compartments, for the first time, we use three different scenarios to account for surface water storage changes before data assimilation (see details in Section 3.1). The main reason for using the W3RA model to perform our investigations is to rely on the physical processes implemented in the model equations to consistently separate GRACE TWS (since both model and observation errors are considered) into different water compartments that includes groundwater and soil moisture. As hydrological models are usually better resolved than GRACE data during the assimilation procedure, observations are downscaled, and therefore, higher spatial resolution estimations of water storages will be available within the study region (see, e.g., Schumacher et al., 2016). Here, we use the ensemble-based sequential technique of the Square Root Analysis (SQRA) filtering scheme (Evensen, 2004) to assimilate GRACE TWS into W3RA. SQRA is preferred over the traditional ensemble Kalman filter since it offers a higher computational speed, simplicity, and independence of observation perturbations. Besides, Khaki et al. (2017a) showed that this method is highly capable of assimilating GRACE TWS data into a hydrological model.

After data assimilation, we investigate the connections between the estimated groundwater and soil moisture storages (from improved model) and both surface water level variations and rainfall from multi-mission satellite remote sensing data over Bangladesh. Satellite radar altimetry products of Jason-1 and -2, and Envisat are used in this study to provide 19 virtual river gauge stations for the period 2003 to 2013 distributed across Bangladesh. Since satellite altimetry was initially designed for ocean studies (Fu and Cazenave, 2013), its observations over inland water bodies must be carefully post processed (Birkett, 1998; Calmant et al., 2008; Khaki et al., 2015). Therefore, the Extrema Retracking (ExtR) technique, proposed by Khaki et al. (2014), is applied to retrack satellite waveform data to improve range estimations and consequently derive better water level estimations.

Further, we apply the statistical method of empirical mode decomposition (EMD, Chen et al., 2007) to explore connections between the groundwater and surface water from the model, rainfall data from the Tropical Rainfall Measuring Mission (TRMM), and retracked surface water heights. EMD is an efficient approach to extract cyclic/semi-cyclic components and is preferred over the classical techniques such as the Fourier analysis (Chen et al., 2007; Pietrafesa et al., 2016).

The remainder of this study is organized as follows: in Section 2, the study area, and datasets are presented. Section 3 provides a brief overview of the data assimilation filtering

methods, the ExtR retarcking method as well as the EMD approach. Results and discussion are presented in Section 4, and the study is concluded in Section 5.

## 2. Study Area and Data

### 2.1. Bangladesh

Bangladesh is located in the Bengal Basin, where the Ganges, Brahmaputra, and the Meghna rivers converge. The average temperature of the country ranges from 17°C to 20.6°C during winter and 26.9°C to 31.1°C during summer (Rajib et al., 2011). Bangladesh is placed in the sub-tropical region with a humid, warm, and tropical climate, which is dominated by a subtropical monsoon originating over the Indian Ocean, which carry warm, moist, and unstable air (Ahmed, 2006; Khandu et al., 2017). An average drought frequency in the country is reported to be equivalent to 2.5 years (Adnan, 1993; Hossain, 1990) when rainfall, as the most important water supply, drops by almost 46% (Dey et al., 2011). The annual precipitation ranges from less than 1500 to ~5000 mm and varies over different parts of the country, e.g., 1276 mm and 1337 mm in the central and western regions, respectively (see, e.g., Hasan et al., 2013; Islam et al., 2014).

FIGURE 1

### 2.2. W3RA Hydrological Model

The globally distributed  $1^\circ \times 1^\circ$  World-Wide Water Resources Assessment system (W3RA) model is used to simulate water storage over Bangladesh. W3RA is a daily grid distributed biophysical model developed in 2008 by the Commonwealth Scientific and Industrial Research Organisation (CSIRO). The model simulates water storage and flows to monitor, represent, and forecast terrestrial water storages (van Dijk, 2010; Renzullo et al., 2014). The meteorological forcing data sets for the model include minimum and maximum temperature, downwelling short-wave radiation, and precipitation from Princeton University (see detail in Sheffield et al., 2006). Effective soil parameters, including water holding capacity, and soil evaporation, related greenness and groundwater recession, and saturated area to catchment characteristics are the model parameters (van Dijk et al., 2013). The model states used in this study include the top, shallow, and deep root soil layers, groundwater storage, and surface water storage in



a one-dimensional system (vertical variability). More detailed information on W3RA can be found in [van Dijk et al. \(2013\)](#).

### 2.3. Remotely Sensed Observations

#### 2.3.1. GRACE

The GRACE level 2 (L2) monthly Stokes' coefficients up to degree and order 90 and their full error information (2003-2013) are obtained from the ITSG-Grace2014 gravity field model ([Mayer-Gürr et al., 2014](#)) and used in the data assimilation process. The monthly full error information of the Stokes' coefficients is used to construct an observation error covariance matrix for the GRACE TWS fields ([Eicker et al., 2014](#); [Schumacher et al., 2016](#)). Note that different GRACE products from various centers can lead to different results depending on their data processing strategies ([Shamsudduha et al., 2017](#)). However, for the sake of data assimilation, in addition to GRACE observations, we also need full error information associated with the observations. [Schumacher et al. \(2016\)](#) and [Khaki et al. \(2017b\)](#) show that it is important to consider GRACE full error covariance matrix to conduct data assimilation experiments. A more comprehensive analysis of different GRACE products has already been performed in a recently published paper of [Schumacher et al. \(2017\)](#). Their results indicate that while using the full covariance matrix in the data assimilation procedure, differences between the GRACE products do not significantly change to affect the final results. Therefore, we only use ITSG-Grace2014 data for which we are sure that the full covariance field is well representative of the GRACE data's error structure.

Degree 1 of Stokes' coefficients are replaced with those estimated by [Swenson et al. \(2008\)](#) to account for the change in the Earth's center of mass. Degree 2 and order 0 (C20) coefficients are replaced by those from Satellite Laser Ranging solutions due to unquantified large uncertainties in this term (e.g., [Cheng and Tapley, 2004](#); [Chen et al., 2007](#)). Colored/correlated noises in the L2 products are reduced using the DDK2 smoothing filter following [Kusche et al. \(2009\)](#). This smoothing causes some degree of signal attenuation ([Klees et al., 2008](#)) and moving anomalies from outside the region (e.g., Bay of Bengal) ([Chen et al., 2007](#); [Khaki et al., 2017d](#)). To mitigate this issue, following [Swenson and Wahr \(2002\)](#), we apply an isotropic kernel using a Lagrange multiplier filter to decrease leakage errors over the entire Bangladesh. This filter uses a basin averaging kernel method expanded in terms of spherical harmonics and subsequently combined with L2 potential coefficients to improve the GRACE estimates (see details in [Swenson and](#)

Wahr, 2002). The L2 gravity fields are then converted to  $1^\circ \times 1^\circ$  TWS fields following Wahr et al. (1998). Note that the GRACE data provide changes in TWS while W3RA produces absolute TWS. Accordingly, the mean TWS for the study period is taken from W3RA and is added to the GRACE TWS change time series to obtain absolute values and make them comparable with model outputs (Zaitchik et al., 2008).

### 2.3.2. Satellite Radar Altimetry

Satellite radar altimetry data of Jason-1 and -2, i.e., 20-Hz sensor geographic data records (SGDR), and Envisat, i.e., 18-Hz SGDR products are applied in this study. The data includes 260 cycles of Jason-1 covering 2002–2008, 166 cycles of Jason-2 covering 2008–2013, and 113 cycles of Envisat covering 2002–2012. Jason-2 is a follow-on mission of Jason-1 with a similar temporal resolution of  $\sim 9.915$  days and the ground cross-track resolution of  $\sim 280$  km (over the equator), with the same characteristics as Topex/Poseidon altimetry mission (Benada, 1997; Papa et al., 2010). Jason-1 and-2 data are obtained from the Physical Oceanography Distributed Active Archive Center (PO.DAAC) and AVISO, respectively. Additionally, Envisat RA2 products with a 35 days repeat cycle (30 days for new orbit after October 2010) are derived from ESA (Table 1).

Altimeter ranges should be corrected for atmospheric impacts such as ionospheric, tropospheric, and electromagnetic effects (Benada, 1997). We apply geophysical correction, including solid earth tide, pole tide, and dry tropospheric (Birkett, 1995) to correct the ranges. The ExtR post-processing technique (Khaki et al., 2014) is applied on waveforms to retrack datasets and improve range measurements. The retracked altimetry data are then used to build virtual time series for 19 different points (Figure 1) located on the satellite ground tracks and distributed throughout the study area. At each virtual point, several points belonging to the same satellite cycle are considered, and the median value of the retracked altimetry-based water levels is computed to address the hooking effect (Frappart et al., 2006). While a satellite is passing above a water body, it is locked over a spatially limited part of the water, which can result in an error. The hooking effect results in incorrect range measurements, known as off-nadir measurements (Seyler et al., 2008; Boergens et al., 2016). Afterwards, time series of water level variations from Jason-1 and -2 are combined with those of Envisat products to produce monthly surface levels. Details of the datasets, model, and pass numbers of the altimetry missions used in this study are presented in Table 1.



### 2.3.3. Precipitation

We use precipitation data of the Tropical Rainfall Measuring Mission Project (TRMM-3B43 products; version 7, [TRMM, 2011](#); [Huffman et al., 2012](#)) to assess climate variability over Bangladesh. Incorporating more microwave sounding and imagery records as well as implementing better processing algorithms have caused a large improvement in this version of data ([Huffman et al., 2012](#); [Fleming and Awange, 2013](#)). The data sets, validated by [Khandu et al. \(2017\)](#) over the study region showed promising performance. The gridded ( $0.25^\circ \times 0.25^\circ$ ) precipitation products (2003 to 2013) are converted to  $1^\circ \times 1^\circ$  and used to investigate their connection to water storage changes.

### 2.4. Surface Storage Data

For the objective of data assimilation, considering that many surface water sources (in different forms, e.g., lakes and rivers except few major ones) are not modeled in W3RA, surface water storages should be removed from GRACE TWS data. To this end, we use satellite-derived surface water data in the Ganges–Brahmaputra River Basin (as the main source of surface water in Bangladesh) provided by [Papa et al. \(2015\)](#). The data is based on a multi-satellite approach that combines surface water extent from the Global Inundation Extent from Multi-Satellite (GIEMS, [Papa et al., 2006, 2010](#); [Prigent et al., 2012](#)) and level height variations of water bodies from Envisat radar altimetry to estimate surface water storage ([Frappart et al., 2012](#)) covering the period from 2003 to 2007. Since study period is 2003 to 2013, canonical correlation analysis is applied to extend the data from 2007 to 2013. Satellite derived river height fluctuations of Section 2.3.2 that are distributed across the study area are used in the process of extending the surface water storage of [Papa et al. \(2015\)](#). More details on the canonical correlation analysis are provided in Section 3.4.

### 2.5. In-situ measurements

To evaluate the performance of data assimilation, in-situ measurements are used. To this end, we use groundwater (198 stations) and soil moisture (12 stations) in-situ measurements of different stations (see Figure 1) provided by the Bangladesh Water Development Board (BWDB) and Institute of Water Modelling (IWM) in [The Asian Development Bank \(2011\)](#). Figure 2 shows the sample products of different groundwater stations, as well as soil moisture variations measured at various depths. Specific yields ranging from 0.01 to 0.2 ([Shamsudduha](#)

et al., 2011; BWDB, 1994) are used to convert well-water levels to variations in groundwater storage. Details of the datasets used in this study are outlined in Table 1.

FIGURE 2

TABLE 1

### 3. Method

#### 3.1. Data Assimilation

##### 3.1.1. Filtering Method

The square root analysis (SQRA) scheme for the Ensemble Kalman Filter (EnKF), presented in Evensen (2004) is used to assimilate the GRACE TWS into W3RA. SQRA, which is a deterministic form of ensemble-based Kalman filters uses a statistical sample of state estimates and unlike traditional Kalman filtering method, does not need an observation perturbation (Burgers et al., 1998; Sakov and Oke, 2008; Khaki et al., 2017a). Instead, by introducing a new sampling scheme, SQRA uses unperturbed observations without imposing any additional approximations like uncorrelated measurement errors (Evensen, 2004). The update stage in SQRA includes two steps starting with updating the ensemble-mean as,

$$\bar{X}^a = \bar{X}^f + K(y - H\bar{X}^f), \quad i = 1 \dots N, \quad (1)$$

$$K = P^f(H)^T(HP^f(H)^T + R)^{-1}, \quad (2)$$

where ‘f’ stands for forecast, ‘a’ for analysis, and  $N$  is the ensemble number.  $\bar{X}^a$  is the mean analysis state,  $K$  represent the Kalman gain, and  $y$  is the observation vector. The transition and observation covariance matrices are indicated by  $H$  and  $R$ , respectively.  $\bar{X}^f$ , the forecast ensemble mean, and the model state forecast error covariance ( $P^f$ ) are derived by,

$$\bar{X}^f = \frac{1}{N} \sum_{i=1}^N (X_i), \quad (3)$$

$$P^f = \frac{1}{N-1} \sum_{i=1}^N (X_i^f - \bar{X}^f)(X_i^f - \bar{X}^f)^T. \quad (4)$$

$$(5)$$

The model state ( $X$ ) contains  $N$  different vectors of the model state variables. Note that  $A^f = [A_1^f \dots A_N^f]$  is the ensemble of anomalies, the deviation of model state ensembles from the ensemble mean ( $A_i^f = X_i^f - \bar{X}^f$ ). In the second update step, SQRA computes the ensemble perturbations through.

$$A^a = A^f V \sqrt{I - \Sigma^T \Sigma \Theta^T}, \quad (6)$$

where  $\Sigma$  and  $V$  are result from singular value decomposition of  $A^f$  ( $A^f = U \Sigma V^T$ ).  $\Gamma$  refers to the singular value decomposition and  $\Theta$  is a random orthogonal matrix (e.g., the right singular vectors from a singular value decomposition of a random  $N \times N$  matrix) for ensemble redistribution of the variance reduction (cf. Evensen, 2004, 2007; Khaki et al., 2017a).

### 3.1.2. Assimilation of GRACE data

To assimilate GRACE TWS into the model, we use a summation of model's vertical water compartments (e.g., soil moisture, groundwater, and surface water) at 13 grid points. This summation is then updated by the GRACE TWS at the same location at every assimilation step (whenever a new observation is available). Initial ensemble members are generated by perturbing the meteorological forcing fields following Renzullo et al. (2014). In this regard, the three most important forcing variables; precipitation, temperature, and radiation are perturbed using Monte Carlo sampling of multivariate normal distribution (with the errors representing the standard deviations) to produce an ensemble (with 72 members as suggested by Oke et al., 2008). The perturbed meteorological forcing datasets are then integrated forward with the model from 2000 to 2003 to provide a set of state vectors at the beginning of the study period.

Two widely used tuning techniques of ensemble inflation and localization are applied to enhance the assimilation performance especially when a limited ensemble size is assumed. Ensemble inflation uses a small coefficient (i.e., 1.12 in our study; Anderson et al., 2001) to inflate prior ensemble deviation from the ensemble-mean to increase their variations and alleviate the inbreeding problem (Anderson et al., 2007). For localization, the Local Analysis (LA) scheme (Evensen, 2003; Ott et al., 2004; Khaki et al., 2017b) is applied. LA restricts the impact of a given measurement in the update step to the points located within a certain distance ( $3^\circ$  following Khaki et al., 2017b) from the measurement location. We also implement three different cases to deal with surface water storage during data assimilation.

- Case 1: Assimilating the GRACE TWS data after removing surface storages into the model states except for the surface water compartment.

• Case 2: Adding surface water storage to model surface water compartment and using the GRACE TWS to update the summations of all water compartments.

• Case 3: Assimilating the GRACE TWS to update the summations of all water compartments (including surface water compartment).

In Section 4.1, the results of all the case scenarios are compared with each other and evaluated against in-situ groundwater measurements.

### 3.2. Empirical Mode Decomposition (EMD)

The empirical mode decomposition (EMD) proposed by [Chen et al. \(2007\)](#) is used for analyzing multivariate datasets of this study. EMD establishes different frequencies and trends within time series, which are called Intrinsic Mode Functions (IMFs), by considering local oscillations ([Rilling et al., 2003](#); [Flandrin et al., 2004](#)). The idea is that a signal is composed of fast oscillations superimposed by slow oscillations ([Flandrin et al., 2004](#)). Thus, EMD decomposes any complicated data set into a finite and often small number of IMFs hidden in the observations ([Huang et al., 1998](#)). We apply EMD on all available time series of this study to extract different frequencies and also to find local trends for a better understanding of their interrelationships.

### 3.3. Retracking Scheme

In this study, we use the retracking method to improve altimetry estimations of river height variations. The retracking process is essential since complex waveform patterns are usually observed over rivers. To this end, Extrema Retracking (ExtR) post-processing technique ([Khaki et al., 2014, 2015](#)) is used. The ExtR is a three step filter that starts by applying a moving average filter to reduce the random noise of the waveforms. It then identifies extremum points of the filtered waveforms, and finally, extracts the main leading edge amongst the established extremum points. The method is applied to process different types of waveforms and improve level estimations as demonstrated in [Khaki et al. \(2014, 2015\)](#). The filter is employed here to retrack satellite radar altimetry data for extracting surface storage from TWS (in Section 3.4). Figure 12 shows river level fluctuations for different parts of Bangladesh (Figure 3a) and the entire area of the country (Figure 3b).

FIGURE 3

### 3.4. Canonical Correlation Analysis (CCA)

Canonical correlation analysis (CCA) seeks to find the linear relationship between two sets of multidimensional variables  $x$  and  $y$ . The process extracts canonical coefficients  $u$  and  $v$  such that  $X = x^T u$  and  $Y = y^T v$  ( $X$  and  $Y$  are canonical variates) possess a maximum correlation coefficient (Chang et al., 2013) using the following function,

$$\begin{aligned} P &= \frac{E[XY]}{\sqrt{E[X^2]E[Y^2]}} \\ &= \frac{E[u^T x y^T v]}{\sqrt{E[u^T x x^T u]E[v^T y y^T v]}} \\ &= \frac{u^T C_{xy} v}{\sqrt{u^T C_{xx} u v^T C_{yy} v}}, \end{aligned} \quad (7)$$

where  $C_{xx}$  and  $C_{yy}$  are covariance matrices of  $x$  and  $y$  respectively and the objective in above function is to maximize the correlation  $P$ . Once the coefficients are calculated, they can be used to find the projection of  $x$  and  $y$  onto  $u$  and  $v$  as canonical variates with maximum correlation. Here,  $x$  contains the vectors of surface water storages from Papa et al. (2015) at each grid point and  $y$  includes river heights variations from satellite radar altimetry in a same temporal scale as the former data (2003 to 2007). After performing canonical correlation analysis, the computed canonical coefficient of  $u$  and  $v$ , and a new set of variables  $y$  (from 2007 to 2013) are used to estimate the canonical variate of  $x$ . The combination of surface water storages ( $x$ ) using the extracted  $u$  from the first part has the maximum correlation to the altimetry-derived river heights variability. Hence, this coefficient vector can be used to transform river heights into surface waters at each grid point.

## 4. Results

### 4.1. Data Assimilation

Before discussing groundwater and soil moisture variations within Bangladesh, the effect of data assimilation on terrestrial water storage time series and its capability to improve model simulations are investigated. Figure 4 shows average TWS time series over Bangladesh before (model-free run) and after data assimilation. The figure also contains GRACE TWS time series. It can be seen that data assimilation largely reduces misfits between model-free run and observations by incorporating GRACE TWS into the states.

FIGURE 4

To assess whether data assimilation (e.g., in Figure 4) can result in better water storage estimates, in-situ groundwater and soil moisture measurements are used for validation. Time series of groundwater and soil moisture anomalies are generated for each station. Groundwater and soil moisture results from all the three assimilation cases (cf. Section 3.1.2) are spatially interpolated using the nearest neighbour (the closest four data values) to the location of the in-situ measurements. This is also done for outputs of the WaterGAP Global Hydrology Model (WGHM; more details on Döll et al., 2003; Müller et al., 2014), as well as estimated storages by van Dijk et al. (2014), indicated here by W3, who merged GRACE observations with a hydrological multi-model ensemble. The comparison between these products and data assimilation results allows us to better investigate any achieved improvements. For this purpose, the RMSE and correlations between in-situ and estimated time series are calculated.

Table 2 summarizes the average RMSE and correlation for each of the three data assimilation case. From Table 2, it can be seen that the groundwater results are more correlated to in-situ measurements after the application of every assimilation case (0.81 on average), 0.39 larger than model simulations without applying data assimilation (model-free run). An average RMSE improvement of 51.16% (at 0.95 confidence level) in case 1 shows a significant influence of the data assimilation scheme, approximately 4.44% and 39.11% larger than cases 2 and 3, respectively. It is also evident from Table 2 that data assimilation results, especially cases 1 and 2 outperform groundwater estimates of WGHM. Note that the provided W3 does not include groundwater and therefore we use it for soil moisture comparison only. Table 2 emphasizes that model groundwater estimations can be successfully improved with respect to the in-situ measurements if they are fine tuned by GRACE data through the assimilation especially for cases 1 and 2.

TABLE 2

Furthermore, correlation analysis is carried out between in-situ soil moisture measurements at various depths and data assimilation results from different scenarios, as well as soil moisture estimates of WGHM and W3 (Table 3). In-situ measurements at different depths are compared with different layers from data assimilation results. For this purpose, in-situ soil moisture time



series of 0–10 cm, 0–30 cm, and 0–50 cm depths are compared to the model top, shallow, and deep soil moisture layers. While the model soil moisture of top layer corresponds to the thickness between 5 and 10 cm, the model shallow and deep-root soil layers broadly represent 10–21 cm and 3–6 m soil thicknesses (see also [Renzullo et al., 2014](#); [Tian et al., 2017](#)). Here, we compare W3RA’s top layer estimations with in-situ of 0–10 cm, top layer plus shallow-root simulations with in-situ of 0–20 cm, and summation of the top, shallow, and a portion of deep-root soil layers with 0–50 cm in-situ measurements. Note that WGHM and W3 outputs are provided at a single aggregated layer and correspondingly are compared with in-situ soil time series at the depth 0–50 cm. Table 3 shows that the highest correlation improvements, 18.31% (on average) for all layers and 25.25% for the deep layer. Case 2 also represents considerable improvements slightly smaller than case 1, still 11.57% larger than case 3, 6.97% larger than WGHM, and 9.25% larger than W3. Both Table 2 and Table 3 demonstrate a high capability of data assimilation in improving model simulations of different compartments. These tables also indicate a better performance of the implemented data assimilation, specifically cases 1 and 2, compared to WGHM and W3.

TABLE 3

To better analyze the differences between each assimilation case, we compare their RMSE during 2007. In 2007, a major flooding (following ENSO rains) occurred across South Asia affecting Bangladesh ([Gaiha et al., 2010](#)). This phenomenon can help us to monitor performances of each case in such an extreme situation and their ability to distribute observed TWS between all water compartments. Groundwater estimates from each case and in-situ measurements are used to calculate RMSE for each assimilation case (Figure 5), where the least errors are estimated by cases 1 and 2. Assimilating the GRACE TWS without considering surface water storage within the area (case 3) causes larger errors especially in April and September. The largest error, however, is obtained for the model-free run. Hereafter, we use the result of data assimilation for case 1 since it performed slightly better than case 2 and significantly better than case 3 in terms of the RMSE (see Figure 5).

FIGURE 5

The model’s water storage variations computed by assimilating GRACE TWS data into

W3RA are presented in Figures 6 and 7. Temporal averages of soil moisture and groundwater storage variations for each grid point from data assimilation, WGHM, and W3 in the study area are displayed in Figures 6 and 7, respectively. We find large correlations between assimilation results and WGHM (0.76 on average for soil moisture and 0.82 on average for groundwater) and W3 (0.71 on average for soil moisture) outputs. The results show more negative groundwater variations within different parts of Bangladesh than soil water storage variations (see Figure 6). Both water compartments indicate larger signals (in terms of amplitude) in the central and northwestern parts of Bangladesh. A positive soil moisture variations are found in the centre toward east and north within the study period, especially for the assimilation and WGHM maps. Larger groundwater variations are also captured in the same area. While assimilation results show negative groundwater changes over the central, eastern, and to a lesser degree southern parts, WGHM only indicates negative variations in the southern and eastern parts. Figure 7 indicate that smaller water storage variations in the northwestern and northeastern parts of Bangladesh during 2003–2013.

FIGURE 6

FIGURE 7

The average time series of soil moisture and groundwater storages from data assimilation are shown in Figures 8a Figure 8b, respectively. We estimate spatial averages for all the time series at grid points for this figure. Figure 8a shows slight declines in the soil water storage after 2007, which can be related to variations of surface water storage in the same period. The correlation between the surface water storage and soil moisture time series (after removing seasonal effects) is found to be 0.92 (for a 95% confidence interval), 34% higher than the correlation between groundwater and soil moisture. This indicates that a stronger connection exists between the surface water storage and soil moisture over the area. Annual variations of groundwater storages, however, show a larger decline in comparison to soil moisture storage variations, especially between 2008 and 2012. A significant decrease in groundwater storage is seen in Figure 8b with an average rate of  $8.73 \pm 2.45$  mm/year, showing an overall  $\sim 46\%$  reduction. The decline in water availability can be due to over-extraction of groundwater resources since such a decrease is not seen in precipitation (see Section 4.2 for more details).

FIGURE 8

#### 4.2. Statistical Analyses

First, the precipitation and TWS over Bangladesh is analyzed. To explore the climate variability and its relationship with water storages, precipitation will be compared to the data assimilation results. Principal component analysis (PCA [Lorenz, 1956](#)) is applied on GRACE TWS and precipitation time series at each grid point to explore their spatio-temporal variations. The first three most dominant empirical orthogonal functions (EOF1, EOF2, EOF3) for each variable are presented in Figure 9. The spatial distribution of precipitation within Bangladesh indicates larger rainfall in south-eastern parts. TWS distribution in EOF2 follows the same pattern. A large water storages are captured by EOF3 in the northwest. More information can be extracted from precipitation and TWS time series. The first three principal components (PC1, PC2, and PC3) of each data set are shown in Figure 10. Large precipitation impacts are found in 2003 and 2007. A negative anomaly in rainfall is found in 2010 and 2012, as well as in the period between 2005 and 2007 (PC1). TWS time series demonstrate declines between 2005 and 2007, and particularly after 2009 following a drop event ([Mondol et al., 2017](#)). Results, however, show an increase in 2007 in agreement with ENSO rainfall. The overall average of TWS variations during the study period is negative ( $\sim 11.48 \pm 3.19$  mm/year) for the entire country. A similar trend, however, is not observed in precipitation even though there is a shorter period negative decline in 2005 and after 2010. Figure 10 illustrates that although in some cases a variation in precipitation results in a changes in TWS, continuous TWS reduction possibly has different explanations that could become clear through the separation of the groundwater and surface water storages (cf. [Section 3.4](#)).

FIGURE 9

FIGURE 10

Details on surface and groundwater storage variations and their relationship to precipitation and rivers' level heights are presented in Table 4. For each grid point in the study area, we calculate water storage variation rates and depletions, and also a correlation coefficient between their time series and both precipitation and river height variations. Note that we use lag-

correlation (cross correlation) to achieve the maximum correlation between each two time series. Table 4 illustrates that there is a water decline in both surface and groundwater storages at different rates. This can be inferred from the negative storage variation rates. An approximately 32% depletion in groundwater storage causes a significant decrease in TWS as shown in Figure 10. This remarkable water reduction, unlike the rainfall pattern, is highly related to excessive groundwater usages, especially for irrigation. It can be concluded from Table 4, therefore, that groundwater storages are less correlated (16.5%) to river height variations and precipitation, respectively, in comparison to surface water storage. Consequently, variations in rainfalls and river heights are more reflected in surface storage variations.

TABLE 4

To better analyze groundwater storage changes, we apply empirical mode decomposition (EMD) on time series in each grid point. EMD is used to extract Intrinsic Mode Functions (IMFs) of time series that are found to be most representative of the initial signals. The relationships between the groundwater IMFs and those of precipitation, TWS, and surface river fluctuations are shown in Figure 11, which contains scatter bi-plots and the interpolated line representing the correspondence between two variables. The trend lines in the sub-figures show that the computed IMFs for the different variables are close to each other. The concentration of distributed points after applying EMD is more symmetric than for the initial time series especially for the groundwater and TWS, as well as the groundwater and water level variations. Table 5 contains the average correlation between the time series of groundwater and the variables of precipitation, TWS, and river height variation. The more symmetric distributed points in between the groundwater IMF and that of GRACE TWS shows the greater relationship between these two variables corresponding to a higher correlation presented in Table 5. The reason for this can be due to the use of GRACE TWS in data assimilation. A higher correlation is also obtained between the IMF of groundwater and those of river height. The least relationship is obtained for the groundwater IMF and precipitation, that implies the different pattern in variations of these two variables, which could be related to the non-climatic effects in the groundwater.

FIGURE 11

TABLE 5

470 The extracted first two IMFs for the groundwater time series are illustrated in Figure 12.  
 471 In the both subfigures, a decline in groundwater storages is observed. Such a trend, however,  
 472 is more significant for IMF 2. We also plot the first and second precipitation's IMFs for  
 473 comparison. The precipitation's IMF 1 in Figure 12, better indicates rainfall variation from  
 474 Figure 10. Two periods with larger rainfall can be seen for the years 2006 and 2009. A decrease  
 475 in rainfall over Bangladesh is found from 2010 onwards, with smaller amplitudes during 2010  
 476 and 2012. This may impact the groundwater levels during similar temporal periods. There  
 477 are several similar patterns in both time series (groundwater and precipitation) especially for  
 478 IMF 1. Both groundwater and precipitation IMFs increase during 2006 and mid-2008 to mid-  
 479 2009. Figure 12b, presenting IMF 2 time series of assimilated groundwater, clearly shows the  
 480 groundwater depletion despite having minimum changes in precipitations. This suggests that  
 481 other factors (e.g., human impacts) affect groundwater storages in Bangladesh.

FIGURE 12

## 482 5. Conclusion

483 Terrestrial waters, as an essential factor for both human life and environment, can be  
 484 affected by climate changes, especially over the south Asian areas. Bangladesh, in particular,  
 485 is a highly vulnerable region in facing climate changes suffering from serious water issues, espe-  
 486 cially for irrigation. In this study, we analyze groundwater variations within Bangladesh using  
 487 multi-mission satellite measurements, as well as by running a hydrological model during 2003 to  
 488 2013. The the Gravity Recovery And Climate Experiment (GRACE) terrestrial water storage  
 489 (TWS) data after removing surface water storages is assimilated into W3RA model using the  
 490 ensemble-based sequential technique of the Square Root Analysis (SQRA) filter. This is done to  
 491 improve the World-Wide Water Resources Assessment system (W3RA) simulations of ground-  
 492 water, as well as soil water storages. We also apply the empirical mode decomposition (EMD)  
 493 on water storages, precipitation, and altimetry-derived rivers level variations time series to ex-  
 494 plore the relationship between them in the area. The larger correlation is found between river  
 495 level heights and rainfalls (78% average) in comparison to groundwater storage variations and

rainfalls (57% average). The considerable difference between correlation coefficients indicates a different impact of rainfall on surface and groundwater variations, which could imply influences of groundwater depletion by population (especially for excessive irrigations) across the country. The results show an approximately 26%, groundwater depletion with a remarkable influence on a total water stored in the area. A significant decline in groundwater storage ( $\sim 32\%$  reduction over the study period) over the country is found by the assimilation results with an average rate of 8.73 mm/year. In the absence of any considerable decrease in precipitation over the region, a remarkable groundwater reduction is observed from the first and second Intrinsic Mode Functions (IMFs), which can be referred to human impacts. High spatio-temporal resolution remote sensing products along with the data assimilation methodology show a high capability for studying water storages in Bangladesh. Developing Earth observation missions dedicated to hydrology (GRACE follow-on and SWOT) can be very important to pursue and improve such modeling and assimilation studies.

## Acknowledgement

We would like to thank Dr. Ashraf Dewan and who provided us valuable groundwater and soil moisture in-situ measurements over Bangladesh. Authors are also grateful to BWDB (<http://www.hydrology.bwdb.gov.bd/>) for in-situ data. M. Khaki is grateful for the research grant of Curtin International Postgraduate Research Scholarships (CIPRS)/ORD Scholarship provided by Curtin University (Australia). This work is a TIGeR publication and supported by the Belmont Forum/G8 Project on coastal vulnerability, in the US via the National Science Foundation (Grant No. ICER-1342644).



## References

- Abdullah Aziz, M., Abul Kashem Majumder, M., Shahjahan Kabir, Md., Ismail Hossain, Md., Farhat Rahman, N.M., Rahman, F., Hosen, S. (2015). Groundwater depletion with expansion of irrigation in Barind Tract: a case study of Rajshahi District of Bangladesh. *Int. J. Geol. Agric. Environ. Sci.* 3, 3238.
- ADB, Technical Assistance Consultant's Report (2011). BANGLADESH: Khulna Water Supply Project (Financed by the Technical Assistance Special Fund), Institute of Water Modelling (IWM), Project Number: P42171-012, <https://www.adb.org/sites/default/files/project-document/77210/42171-012-ban-tacr-01.pdf>.
- Adhikary, S.K., Das, S.K., Saha, G.C., Chaki, T. (2013). Groundwater Drought Assessment for Barind Irrigation Project in Northwestern Bangladesh, 20th International Congress on Modelling and Simulation, Adelaide, Australia, [www.mssanz.org.au/modsim2013](http://www.mssanz.org.au/modsim2013).
- Adnan, S. (1993). Living without floods: lessons from the drought of 1992, Research and Advisory Services, Dhaka.
- Ahmed, U.A. (2006). Bangladesh climate change impacts and vulnerability: A synthesis. Climate Change Cell, Department of Environment Component 4b, Comprehensive Disaster Management Programme, Bangladesh.
- Alimuzzaman, U.A. (2017). Study of Ground Water Recharge from Rainfall in Dhaka City. *International Journal of Science and Engineering Investigations*, vol. 6, issue 6, ISSN: 2251-8843.
- Anderson, J. (2001). An Ensemble Adjustment Kalman Filter for Data Assimilation. *Mon. Wea. Rev.*, 129, 2884-2903, [http://dx.doi.org/10.1175/1520-0493\(2001\)129<2884:AEAKFF>2.0.CO;2](http://dx.doi.org/10.1175/1520-0493(2001)129<2884:AEAKFF>2.0.CO;2).
- Anderson, M.C., Norman, J.M., Mecikalski, J.R., Otkin, J.A., Kustas, W.P. (2007). A climatological study of evapotranspiration and moisture stress across the continental United States based on thermal remote sensing: 1. Model formulation. *J. Geophys. Res.* 112 (D10117). <http://dx.doi.org/10.1029/2006JD007506>.

544 BWDB (Bangladesh Water Development Board) (1994). Report on the compilation of aquifer  
545 test analysis results, BWDB Water Supply Paper 534, Ground Water Circle II, BWDB,  
546 Dhaka.

547 Benada, J.R. (1997). PODAAC Merged GDR (TOPEX/POSEIDON) Generation B User's  
548 Handbook, Version 2.0. JPL D-11007. Pasadena: Jet Propulsion Laboratory, California In-  
549 stitute of Technology.

550 Bennett, A.F. (2002); Inverse Modeling of the Ocean and Atmosphere, 234 pp., Cambridge  
551 Univ. Press, New York.

552 Bertino, L., Evensen G., Wackernagel, H. (2003). Sequential Data Assimilation Techniques in  
553 Oceanography, International Statistical Review, Vol. 71, No. 2 (Aug., 2003), pp. 223-241.

554 Birkett, C.M. (1995). The Contribution of TOPEX/POSEIDON to the Global Monitoring of  
555 Climatically Sensitive Lakes. Journal of Geophysical Research 25: 17925.

556 Birkett, C.M. (1998). Contribution of the TOPEX NASA radar altimeter to the  
557 global monitoring of large rivers and wetlands, Water Resour. Res., 34(5), 1223-1239,  
558 <http://dx.doi.org/10.1029/98WR00124>.

559 Boergens, E., Dettmering, D., Schwatke, C., Seitz, F. (2016). Treating the Hooking Effect in  
560 Satellite Altimetry Data: A Case Study along the Mekong River and Its Tributaries. Remote  
561 Sens., 8, 91, <http://dx.doi.org/10.3390/rs8020091>.

562 Brown, G.S. (1977). The Average Impulse Response of a Rough Surface and Its Applications.  
563 IEEE Transactions on Antennas and Propagation 25: 6774.

564 Burgers, G., van Leeuwen, P.J., Evensen, G. (1998). Analysis scheme in the ensemble Kalman  
565 filter, Mon. Wea. Rev., 126, 1719-1724.

566 Calmant, S., Seyler, F., Crtaux, J.F. (2008). Monitoring continental surface waters by satellite  
567 altimetry, Surv. Geophys., 29(45), 2472-69, <http://dx.doi.org/10.1007/s10712-008-9051-1>.

568 Chang, B., Kruger, U., Kustra, R., Zhang, J. (2013). Canonical Correlation Analysis based  
569 on Hilbert-Schmidt Independence Criterion and Centered Kernel Target Alignment, Volume  
570 28: Proceedings of The 30th International Conference on Machine Learning, 2, 28, 316-324,  
571 <http://jmlr.csail.mit.edu/proceedings/papers/v28/chang13.pdf>.

572 Chen, J.L., Wilson, C.R., Famiglietti, J.S., Rodell, M. (2007). Attenuation effect on seasonal  
573 basin-scale water storage changes from GRACE time-variable gravity. *Journal of Geodesy*,  
574 81, 4, 237245. <http://dx.doi.org/10.1007/s00190-006-0104-2>.

575 Cheng, M.K., Tapley, B.D. (2004). Variations in the Earth's oblateness during  
576 the past 28 years. *Journal of Geophysical Research, Solid Earth*, 109, B09402.  
577 <http://dx.doi.org/10.1029/2004JB003028>.

578 Dey, N.C., Alam, M.S., Sajjan, A.K., Bhuiyan, M.A., Ghose, L., Ibaraki, Y., Karim, F. (2011).  
579 Assessing Environmental and Health Impact of Drought in the Northwest Bangladesh, *J.*  
580 *Environ. Sci. & Natural Resources*, 4(2): 89-97, <http://dx.doi.org/10.3329/jesnr.v4i2.10141>.

581 Döll, P., Kaspar, F., Lehner, B. (2003). A global hydrological model for deriving water avail-  
582 ability indicators: model tuning and validation, *J. Hydrol.*, 270, 105134.

583 Eicker, A., Schumacher, M., Kusche, J., Dll, P., Mller-Schmied, H. (2014). Calibration/data  
584 assimilation approach for integrating GRACE data into the WaterGAP global hydrology  
585 model (WGHM) using an ensemble Kalman filter: first results, *SurvGeophys*, 35(6):12851309.  
586 <http://dx.doi.org/10.1007/s10712-014-9309-8>.

587 Elbern, H., Schmidt, H. (2001). Ozone episode analysis by four dimensional variational chem-  
588 istry data assimilation, *J. Geophys. Res.*, 106, 35693590.

589 Evensen, G. (2003). The ensemble Kalman filter: Theoretical formulation and practical imple-  
590 mentation, *Ocean Dynamics*, 53, 343367, <http://dx.doi.org/10.1007/s10236-003-0036-9>.

591 Evensen, G. (2004). Sampling strategies and square root analysis schemes for the EnKF. *Ocean*  
592 *Dyn.* 54(6), 539-560.

593 Evensen, G. (2007). *Data Assimilation: The Ensemble Kalman Filter*, Springer, 279 pp.

594 Flandrin, P., Gonalvs, P., Rilling, G. (2004). Detrending and denoising with empirical mode  
595 decompositions, 12th European Signal Processing Conference, Vienna, 2004, pp. 1581-1584.

596 Fleming, K., Awange, J.L. (2013). Comparing the version 7 TRMM 3B43 monthly precipita-  
597 tion product with the TRMM 3B43 version 6/6A and Bureau of Meteorology datasets for  
598 Australia. - *Australian Meteorological and Oceanographic Journal*, 63, 3, pp. 421426.

599 Forootan, E., Rietbroek, R., Kusche, J., Sharifi, M.A., Awange, J., Schmidt, M., Omondi,  
600 P., Famiglietti, J. (2014). Separation of large scale water storage patterns over Iran using  
601 GRACE, altimetry and hydrological data. *Journal of Remote Sensing of Environment*, 140,  
602 580-595, <http://doi.org/10.1016/j.rse.2013.09.025>.

603 Frappart, F., Calmant, S., Cauhope, M., Seyler, F., Cazenave, A. (2006). Preliminary results  
604 of envisat ra-2-derived water levels validation over the amazon basin, *Remote Sensing of*  
605 *Environment*, 100(2), 252-264.

606 Frappart, F., Papa, F., Santos da Silva, J., Ramillien, G., Prigent, C., Seyler, F., Calmant,  
607 S. (2012). Surface freshwater storage and dynamics in the Amazon basin during the 2005  
608 exceptional drought, *Environ. Res. Lett.*, 7, 044010 (7pp), [http://dx.doi.org/10.1088/1748-](http://dx.doi.org/10.1088/1748-9326/7/4/044010)  
609 [9326/7/4/044010](http://dx.doi.org/10.1088/1748-9326/7/4/044010)

610 Fu, L.L., Cazenave, A. (2001). *Satellite altimetry and Earth sciences, A Handbook of techniques*  
611 *and applications. International Geophysics Series*, 69, Academic, San Diego.

612 Garner, T.W., Wolf, R.A., Spiro, R.W., Thomsen, M.F. (1999). First attempt at assimilating  
613 data to constrain a magnetospheric model, *J. Geophys. Res.*, 104(A11), 25145-25152,  
614 <http://dx.doi.org/10.1029/1999JA900274>.

615 Gaiha, R., Hill, K., Thapa, G. (2010). *Natural Disasters in South Asia*, ASARC Work-  
616 ing Papers, The Australian National University, Australia South Asia Research Centre,  
617 <http://EconPapers.repec.org/RePEc:pas:asarcc:2010-06>.

618 Hasan, M.R., Mostafa, M.G., Matin, I. (2013). Effect Of Rainfall On Groundwater Level Fluc-  
619 tuations In Chapai Nawabgonj District. *International Journal of Engineering Research &*  
620 *Technology (IJERT)*, Vol. 2 Issue 4, ISSN: 2278-0181.

621 Hossain, M. (1990). Natural calamities, instability in production and food policy in Bangladesh,  
622 *The Bangladesh Development Studies (BDS)*; Bangladesh Institute of Development Studies,  
623 18(1).

624 Hoteit, I., Luo, X., Pham, D.T. (2012). Particle Kalman Filtering: A Nonlinear Bayesian  
625 Framework for Ensemble Kalman Filters, *Monthly Weather Review*, 140:2, 528-542.

- 626 Huang, N.E., Shen, Z., Long, S.R., Wu, M.C., Shih, H.H., et al. (1998). The empirical mode  
627 decomposition and the Hilbert spectrum for nonlinear and non-stationary time series analysis.  
628 Proceedings of the Royal Society of London A 454: 903-995.
- 629 Huffman, G., Bolvin, D. (2012). TRMM and other data precipitation data set documenta-  
630 tion. Mesoscale Atmospheric Processes Laboratory, NASA Goddard Space Flight Center and  
631 Science Systems and Applications, Inc.
- 632 Huntington, T.G., (2006). Evidence for intensification of the global water cycle: Review and  
633 synthesis, J. Hydrol., 319(14), 8395, <http://dx.doi.org/10.1016/j.jhydrol.2005.07.003>.
- 634 Islam, M.S., Alam, M.K., Rahman, M.A. (2013). Groundwater Dynamics in Pabna District,  
635 Bangladesh. IOSR Journal Of Environmental Science, Toxicology And Food Technology  
636 (IOSR-JESTFT) e-ISSN: 2319-2402,p- ISSN: 2319-2399. Volume 4, Issue 2 (May. - Jun.  
637 2013), PP 65-72.
- 638 Islam, M.N., Chowdhury, A., Islam, K.M., Rahaman, M.Z. (2014). Development of rainfall  
639 recharge model for natural groundwater recharge estimation in Godagari Upazila of Ra-  
640 jshahi district, Bangladesh. American Journal of Civil Engineering. Vol. 2, No. 2, pp. 48-52.,  
641 <http://dx.doi.org/10.11648/j.ajce.20140202.16>.
- 642 Kanoua, W., Merkel, B.J. (2015). Groundwater recharge in Titas Upazila in Bangladesh. Arab  
643 J Geosci 8: 1361. <http://dx.doi.org/10.1007/s12517-014-1305-2>.
- 644 Khaki, M., Forootan, E., Sharifi, M.A. (2014). Satellite radar altimetry wave-  
645 form retracking over the Caspian Sea. Int. J. Remote Sens., 35(17), 63296356,  
646 <http://dx.doi.org/10.1080/01431161.2014.951741>.
- 647 Khaki, M., Forootan, E., Sharifi, M.A., Awange, J., Kuhn, M. (2015). Improved grav-  
648 ity anomaly fields from retracked multimission satellite radar altimetry observations  
649 over the Persian Gulf and the Caspian Sea. Geophys. J. Int. 202 (3): 1522-1534,  
650 <http://dx.doi.org/10.1093/gji/ggv240>.
- 651 Khaki, M., Hoteit, I., Kuhn, M., Awange, J., Forootan, E., van Dijk, A.I.J.M., Schumacher,  
652 M., Pattiaratchi, C. (2017a). Assessing sequential data assimilation techniques for integrating  
653 GRACE data into a hydrological model, Advances in Water Resources, Volume 107, 2017,  
654 Pages 301-316, ISSN 0309-1708, <http://dx.doi.org/10.1016/j.advwatres.2017.07.001>.

655 Khaki, M., Schumacher, M., J., Forootan, Kuhn, M., Awange, E., van Dijk, A.I.J.M. (2017b).  
656 Accounting for Spatial Correlation Errors in the Assimilation of GRACE into Hydrological  
657 Models through localization, *Advances in Water Resources*, Available online 1 August 2017,  
658 ISSN 0309-1708, <https://doi.org/10.1016/j.advwatres.2017.07.024>.

659 Khaki, M., Ait-El-Fquih, B., Hoteit, I., Forootan, E., Awange, J., Kuhn, M. (2017c). A two-  
660 update ensemble Kalman filter for land hydrological data assimilation with an uncertain  
661 constraint, In *Journal of Hydrology*, Volume 555, 2017, Pages 447-462, ISSN 0022-1694,  
662 <https://doi.org/10.1016/j.jhydrol.2017.10.032>.

663 Khaki, M., Forootan, E., Kuhn, M., Awange, J., Longuevergne, L., Wada, W. (2017d). Efficient  
664 basin scale filtering of GRACE satellite products, In *Remote Sensing of Environment*, Volume  
665 204, 2018, Pages 76-93, ISSN 0034-4257, <https://doi.org/10.1016/j.rse.2017.10.040>.

666 Khandu, Awange, J.L., Kuhn, M., Anyah, R., Forootan, E. (2017). Changes and  
667 variability of precipitation and temperature in the GangesBrahmaputraMeghna River  
668 Basin based on global high-resolution reanalyses. *Int. J. Climatol.*, 37: 21412159,  
669 <http://dx.doi.org/10.1002/joc.4842>.

670 Klees, R., Revtova, E.A., Gunter, B.C., Ditmar, P., Oudman, E., Winsemius, H.C. (2008).  
671 The design of an optimal filter for monthly GRACE gravity models. *Geophysical Journal*  
672 *International*, 175, 2, 417-432, <http://dx.doi.org/10.1111/j.1365-246X.2008.03922.x>.

673 Knappett, P.S.K., Mailloux, B.J., Choudhury, I., Khan, M.R., Michael, H.A., Barua, S., Mon-  
674 dal, D.R., Steckler, M.S., Akhter, S.H., Ahmed, K.M., Bostick, B., Harvey, C.F., Sham-  
675 sudduha, M., Shuai, P., Mihajlov, I., Mozumder, R., van Geen, A., (2016). Vulnerability of  
676 low-arsenic aquifers to municipal pumping in Bangladesh. *Journal of Hydrology*, 539, 674-686.

677 Kusche, J., Schmidt R., Petrovic, S., Rietbroek, R. (2009). Decorrelated GRACE time-variable  
678 gravity solutions by GFZ and their validation using a hydrological model, *Journal of Geodesy*,  
679 DOI 10.1007/s00190-009-0308-3.

680 Kusche, J., Klemann, V., Bosch, W. (2012). Mass distribution and mass transport in the Earth  
681 system. *Journal of Geodynamics*, 59-60, 1-8. <http://doi.org/10.1016/j.jog.2012.03.003>.

682 Longuevergne, L., Wilson, C.R., Scanlon, B.R., Crtaux, J.F. (2013). GRACE water storage



estimates for the Middle East and other regions with significant reservoir and lake storage.  
Hydrol. Earth Syst. Sci., 17, 48174830, <http://dx.doi.org/10.5194/hess-17-4817-2013>.

Lorenz, E. (1956). Empirical orthogonal function and statistical weather prediction. Technical Report Science Report No 1, Statistical Forecasting Project. MIT, Cambridge.

Mainuddin, M. (2002). Groundwater irrigation in Bangladesh: ‘Tool for Poverty Alleviation’ or ‘Cause of Mass Poisoning’?, Proceedings of the Symposium on Intensive Use of Groundwater: Challenges and Opportunities, Valencia, Spain, 10-14.

Mondol, A.H., Ara, I., Das, S.C. (2017). Meteorological Drought Index Mapping in Bangladesh Using Standardized Precipitation Index during 19812010, Advances in Meteorology, vol. 2017, Article ID 4642060, <http://dx.doi.org/10.1155/2017/4642060>.

Mayer-Gürr, T., Zehentner, N., Klinger, B., Kvas, A. (2014). ITSG-Grace2014: a new GRACE gravity field release computed in Graz. - in: GRACE Science Team Meeting (GSTM), Potsdam am: 29.09.2014.

McBean, E., deJong, A., Gharabaghi, B. (2011). Groundwater in Bangladesh: Implications in a Climate-Changing World, Water Research & Management, Vol. 1, No. 3, pp 3-8.

McCarthy, J.J., Canziani, O.F., Leary, N.A., Dokken, D.J., White, K.S., et al. (2001). Climate Change 2001: Impacts, Adaptation. and Vulnerability, Inter-Governmental Panel on Climate Change (IPCC), Work Group II Input to the Third Assessment Report, Cambridge University Press, Cambridge.

Moradkhani, H., Hsu, K.L., Gupta, H., Sorooshian, S. (2005). Uncertainty assessment of hydrologic model states and parameters: Sequential data assimilation using the particle filter, Water Resour. Res., 41, W05012.

Müller Schmied, H., S. Eisner, D. Franz, M. Wattenbach, F. Portmann, M. Flrke, and P. Dll (2014), Sensitivity of simulated global-scale freshwater fluxes and storages to input data, hydrological model structure, human water use and calibration, Hydrol. Earth. Syst. Sci., 18, 35113538, <http://dx.doi.org/10.5194/hess-18-3511-2014>.

Ott, E., Hunt, B.R., Szunyogh, I., Zimin, A.V., Kostelich, E.J., Corazza, M., Kalnay, E., Patil, D.J., Yorke, J.A. (2004). A local ensemble Kalman Filter for atmospheric data assimilation. Tellus, 56A: 415-428.

Oke, P.R., Brassington, G.B., Griffin, D.A., Schiller, A. (2008). The Bluelink Ocean Data Assimilation System (BODAS). Ocean Modelling, 21, 4670, <http://dx.doi.org/10.1016/j.ocemod.2007.11.002>.

Papa, F., Prigent, C., Durand, F., Rossow, W.B. (2006). Wetland dynamics using a suite of satellite observations: A case study of application and evaluation for the Indian Subcontinent, Geophys. Res. Lett., 33, <http://dx.doi.org/10.1029/2006GL025767>.

Papa, F., Durand, F., Rossow, W.B., Rahman A., Bala, S.K. (2010a). Seasonal and Interannual Variations of the Ganges-Brahmaputra River Discharge, 1993-2008 from satellite altimeters, J. Geophys. Res., 115, C12013, <http://dx.doi.org/10.1029/2009JC006075>.

Papa, F., Prigent, C., Aires, F., Jimenez, C., Rossow, W.B., Matthews, E. (2010b). Interannual variability of surface water extent at global scale, 1993-2004. J. Geophys. Res., 115, D12111, <http://dx.doi.org/10.1029/2009JD012674>.

Papa, F., Frappart, F., Malbeteau, Y., Shamsudduha, M., Vuruputur, V., et al. (2015). Satellite-derived surface and sub-surface water storage in the GangesBrahmaputra River Basin, Journal of Hydrology: Regional Studies, Volume 4, Part A, Pages 15-35, ISSN 2214-5818, <http://dx.doi.org/10.1016/j.ejrh.2015.03.004>.

Pietrafesa, L.J., Shaowu, B., Huang, N.E., Gayes, P.T, Yan, T., et al. (2016). Great Lakes Water Levels: Decomposing Time Series for Attribution. J Climatol Weather Forecasting 4: 153, <http://dx.doi.org/10.4172/2332-2594.1000153>.

Prigent C., Papa, F., Aires, F., Jimenez, C., Rossow, W.B., Matthews, E. (2012). Changes in land surface water dynamics since the 1990s and relation to population pressure, Geophys. Res. Lett., 39, L08403, <http://dx.doi.org/10.1029/2012GL051276>.

Qureshi, A.S., Ahmad, Z.U., Krupnik, T.J. (2015). Moving from resource development to resource management: problems prospects and policy recommendations for sustainable groundwater management in Bangladesh. Water Res. Manage., 29:42694283.

Rafiuddin, M., Uyeda, H. Islam, M.N. (2010). Characteristics of monsoon precipitation systems in and around Bangladesh. Int. J. Climatol., 30: 10421055, <http://dx.doi.org/10.1002/joc.1949>.

- 740 Rajib, M.A., Mortuza, M.R., Selmi, S., Asif Khan Ankur, A.K., et al. (2011). Increase of heat  
741 index over Bangladesh: impact of climate change. *World Academy of Science, Engineering  
742 and Technology* 5(10), pp 340-343.
- 743 Reager, J.T., Thomas, A.C., Sproles, E.A., Rodell, M., Beaudoin, H.K., Li, B., Famiglietti,  
744 J.S., (2015). Assimilation of GRACE Terrestrial Water Storage Observations into a Land  
745 Surface Model for the Assessment of Regional Flood Potential. *Remote Sens.* 2015, 7, 14663-  
746 14679.
- 747 Renzullo, L.J., Van Dijk, A.I.J.M., Perraud, J.M., Collins, D., Henderson, B., Jin, H., Smith,  
748 A.B., McJannet, D.L. (2014). Continental satellite soil moisture data assimilation improves  
749 root-zone moisture analysis for water resources assessment. *J. Hydrol.*, 519, 27472762.  
750 <http://dx.doi.org/10.1016/j.jhydrol.2014.08.008>.
- 751 Rilling, G., Flandrin, P., Goncalves, P. (2003). On empirical mode decomposition and its algo-  
752 rithms. in: *Proceedings IEEE-EURASIP Workshop on Nonlinear Signal and Image Process-  
753 ing NSIP-03, Grado I*, p. 3.
- 754 Rodell, M., Chen, J., Kato, H., Famiglietti, J.S., Nigro, J., Wilson, C.R., (2007). Estimating  
755 groundwater storage changes in the Mississippi River basin (USA) using GRACE. *Hydrogeol.  
756 J.*, 15, 159166.
- 757 Sakov, P., Oke, P.R. (2008). A deterministic formulation of the ensemble Kalman filter: an  
758 alternative to ensemble square root filters, *Tellus* 60A, 361371.
- 759 Sengupta, S, Kang, A., Jacob, N. (2013). *Water Wealth a Briefing Paper on  
760 the State of Groundwater Management in Bangladesh*. India Environment Portal,  
761 [http://www.cseindia.org/userfiles/groundwater\\_management\\_bangladesh.pdf](http://www.cseindia.org/userfiles/groundwater_management_bangladesh.pdf).
- 762 Seyler, F., Calmant, S., Santos da Silva, J., Filizola, N., Roux, E., Cochonneau, G., Vauchel,  
763 P., Bonnet, M.-P. (2008). Monitoring water level in large trans-boundary ungauged basins  
764 with altimetry: the example of ENVISAT over the Amazon basin. *Journal of Applied Remote  
765 Sensing*, 7150: 715017, <http://dx.doi.org/10.1117/12.813258>.
- 766 Shahid, S. (2010). Rainfall variability and the trends of wet and dry periods in Bangladesh. *Int.  
767 J. Climatol.*, 30: 22992313, <http://dx.doi.org/10.1002/joc.2053>.

768 Sheffield, J., Goteti, G., Wood, E.F. (2006). Development of a 50-year high-resolution global  
769 dataset of meteorological forcings for land surface modeling, *J. Clim.*, 19(13), 3088-3111.

770 Shamsudduha, M., Chandler, R.E., Taylor, R.G., Ahmed, K.M., (2009). Recent trends in  
771 groundwater levels in a highly seasonal hydrological system: the Ganges-Brahmaputra-  
772 Meghna Delta. *Hydrology and Earth System Sciences*, 13, 2373-2385.

773 Shamsudduha, M., Taylor, R.G., Ahmed, K.M., Zahid, A., (2011). The impact of intensive  
774 groundwater abstraction on recharge to a shallow regional aquifer system: evidence from  
775 Bangladesh, *Hydrogeology Journal*, 19: 901, <https://doi.org/10.1007/s10040-011-0723-4>.

776 Shamsudduha, M., Taylor, R.G., Longuevergne, L., (2012). Monitoring groundwater storage  
777 changes in the highly seasonal humid tropics: Validation of GRACE measurements in the  
778 Bengal Basin. *Water Resour. Res.*, 48, W02508, <http://dx.doi.org/10.1029/2011WR010993>.

779 Shamsudduha, M., Taylor, R.G., Jones, D., Longuevergne, L., Owor, M., Tindimugaya, C.,  
780 (2017). Recent changes in terrestrial water storage in the Upper Nile Basin: an evaluation  
781 of commonly used gridded GRACE products. *Hydrology and Earth System Sciences*, 21,  
782 4533-4549, <http://dx.doi.org/10.5194/hess-21-4533-2017>.

783 Schumacher, M., Kusche, J., Dll, P. (2016). A systematic impact assessment of GRACE  
784 error correlation on data assimilation in hydrological models, *Journal of Geodesy*,  
785 <http://dx.doi.org/10.1007/s00190-016-0892-y>.

786 Schumacher, M., Forootan, E., van Dijk, A.I.J.M., Mller Schmied, H., Crosbie, R.S., Kusche,  
787 J., Dll, P., (2017). Exploring the hydrological millennium drought pattern (2003-2009) in the  
788 Murray-Darling Basin by assimilating GRACE into WGHM. *Remote Sensing of Environment*,  
789 <http://dx.doi.org/10.1016/j.rse.2017.10.029>.

790 Sumon, F.R., Abul Kalam, A.K.M. (2014). Rainwater Harvesting and the Scope of Enhancing  
791 Ground Water Table in Dhaka City. Dhaka Metropolitan Development Area and Its Planning  
792 Problems, Issues and Policies. Bangladesh Institute of Planners (BIP) Available through.

793 Swenson, S., Wahr, J. (2002). Methods for inferring regional surface-mass anomalies from Grav-  
794 ity Recovery and Climate Experiment (GRACE) measurements of time-variable gravity. *Jour-  
795 nal of Geophysical research*, 107, B9, 2193. <http://dx.doi.org/10.1029/2001JB000576>.

- Swenson, S., Chambers, D., Wahr, J. (2008). Estimating geocenter variations from a combination of GRACE and ocean model output. *Journal of Geophysical research*, 113, B08410, <http://dx.doi.org/10.1029/2007JB005338>.
- Tangdamrongsab, N., Steele-Dunne, S.C., Gunter, B.C., Ditmar, P.G., and Weerts, A.H. (2015). Data assimilation of GRACE terrestrial water storage estimates into a regional hydrological model of the Rhine River basin, *Hydrol. Earth Syst. Sci.*, 19, 2079-2100, <http://dx.doi.org/10.5194/hess-19-2079-2015>.
- Thomas, A.C., Reager, J.T., Famiglietti, J.S., Rodell, M. (2014). A GRACE-based water storage deficit approach for hydrological drought characterization. *Geophys. Res. Lett.* 41, 15371545.
- Tian, S., Tregoning, P., Renzullo, L.J., van Dijk, A.I.J.M., Walker, J.P., Pauwels, V.R.N., Allgeyer, S. (2017). Improved water balance component estimates through joint assimilation of GRACE water storage and SMOS soil moisture retrievals, *Water Resour. Res.*, 53, <http://dx.doi.org/10.1002/2016WR019641>.
- Tropical Rainfall Measuring Mission (TRMM) (2011). TRMM (TMPA/3B43) Rainfall Estimate L3 1 month 0.25 degree x 0.25 degree V7, Greenbelt, MD, Goddard Earth Sciences Data and Information Services Center (GES DISC), Accessed [Data Access Date] [https://disc.gsfc.nasa.gov/datacollection/TRMM\\_3B43\\_7.html](https://disc.gsfc.nasa.gov/datacollection/TRMM_3B43_7.html).
- van Dijk, A.I.J.M. (2010). The Australian Water Resources Assessment System: Technical Report 3, Landscape model (version 0.5) Technical Description, CSIRO: Water for a Healthy Country National Research Flagship.
- van Dijk, A.I.J.M., Renzullo, L.J., and Rodell, M. (2011). Use of Gravity Recovery and Climate Experiment terrestrial water storage retrievals to evaluate model estimates by the Australian water resources assessment system, *Water Resour. Res.*, 47, W11524, <http://dx.doi.org/10.1029/2011WR010714>.
- van Dijk, A.I.J.M., Pea-Arancibia, J.L., Wood, E.F., Sheffield, J., Beck, H.E. (2013). Global analysis of seasonal streamflow predictability using an ensemble prediction system and observations from 6192 small catchments worldwide, *Water Resour. Res.*, 49, 27292746, <http://dx.doi.org/10.1002/wrcr.20251>.

825 van Dijk, A.I.J.M., Renzullo, L.J., Wada, Y., Tregoning, P. (2014). A global water cycle reanal-  
826 ysis (2003-2012) merging satellite gravimetry and altimetry observations with a hydrological  
827 multi-model ensemble. *Hydrol Earth Syst Sci* 18:2955-2973, [http://dx.doi.org/10.5194/hess-](http://dx.doi.org/10.5194/hess-18-2955-2014)  
828 18-2955-2014.

829 Vrugt, J.A., ter Braak, C.J.F., Diks, C.G.H., Schoups, G. (2013). Advancing hydrologic data  
830 assimilation using particle Markov chain Monte Carlo simulation: theory, concepts and  
831 applications, *Advances in Water Resources*, Anniversary Issue - 35 Years, 51, 457-478,  
832 <http://dx.doi.org/10.1016/j.advwatres.2012.04.002>.

833 Wahr, J.M., Molenaar, M., Bryan, F. (1998). Time variability of the Earth's gravity field:  
834 hydrological and oceanic effects and their possible detection using GRACE. *J Geophys Res*  
835 108(B12):30205-30229, <http://dx.doi.org/10.1029/98JB02844>.

836 Wang, B., Ding Q. (2006). Changes in global monsoon precipitation over the past 56 years,  
837 *Geophys. Res. Lett.*, 33, L06711, <http://dx.doi.org/10.1029/2005GL025347>.

838 Wooldridge, S.A., Kalma, J.D. (2001). Regional-scale hydrological modelling using multiple-  
839 parameter landscape zones and a quasi-distributed water balance model. *Hydrological Earth*  
840 *System Sciences*. 5: 59-74.

841 Wouters, B., Bonin, J.A., Chambers, D.P., Riva, R.E. M., Sasgen, I., Wahr, J. (2014). GRACE,  
842 time-varying gravity, Earth system dynamics and climate change. *Reports on Progress in*  
843 *Physics*, 77, 11, 116801. <http://dx.doi.org/10.1088/0034-4885/77/11/116801>.

844 Zaitchik, B.F., Rodell, M., Reichle, R.H. (2008). Assimilation of GRACE terrestrial water stor-  
845 age data into a land surface model: results for the Mississippi River Basin. *J Hydrometeorol*  
846 9(3):535-548, <http://dx.doi.org/10.1175/2007JHM951.1>.






Figure 1: The study area is represented by black solid line. The figure also contains the locations of virtual stations for satellite altimetry time series and various in-situ stations.




Figure 2: (a): In-situ groundwater level variations of various stations. (b): Soil moisture variations at deferent depths belong to Rajshahi in-situ station.




Figure 3: Average river height variation time series from satellite radar altimetry for different parts (a) and for the entire area (b) of Bangladesh. The average error for each measurement is presented as error bars.




Figure 4: Average TWS change time series from data assimilation (case 1), model-free run, and GRACE.




Figure 5: Comparison between RMSE achieved from implementing each data assimilation scenario as well as model-free run during 2007. In case 1, surface storages is removed from GRACE TWS, in case 2, surface storages is added to W3RA surface water, and case 3 refers to the data assimilation with no surface storage correction.




Figure 6: Spatial distribution of average soil water storage variations from data assimilation, WGHM, and W3.




Figure 7: Spatial distribution of average groundwater storage variations from data assimilation and WGHM.




Figure 8: Average soil moisture storage (a) and groundwater storage (b) time series from assimilation, WGHM, W3, and in-situ measurements.






Figure 9: Spatial distribution of of EOF1, EOF2, and EOF3 from applying PCA on precipitation and GRACE TWS.




Figure 10: The first three principal components from applying PCA on precipitation and GRACE TWS.




Figure 11: Relationships between normalized Intrinsic Mode Functions (IMF) time series of groundwater and precipitation, TWS, and surface river height.




Figure 12: The first and second extracted Intrinsic Mode Functions (IMF) time series of the groundwater storage (red) and precipitation (blue).

Table 1: A summary of the datasets used in this study.

Description	Platform	Detail	Data access
Terrestrial water storage (TWS)	GRACE	GRACE level 2 (L2)	<a href="https://www.tugraz.at/institute/ifg/downloads/gravity-field-models/itsg-grace2014/">https://www.tugraz.at/institute/ifg/downloads/gravity-field-models/itsg-grace2014/</a>
Altimetry-derived level height	Jason-1	Pass numbers 90 and 231	<a href="http://podaac.jpl.nasa.gov">http://podaac.jpl.nasa.gov</a>
	Jason-2	Pass numbers 90 and 231	<a href="http://avisoftp.cnes.fr/">http://avisoftp.cnes.fr/</a>
	Envisat	Pass numbers 337, 438, 795, 896, and 982	<a href="http://envisat.esa.int/dataproducts/ra2-mwr/">http://envisat.esa.int/dataproducts/ra2-mwr/</a>
Precipitation	TRMM-3B42	Daily accumulated precipitation	<a href="http://disc2.gesdisc.eosdis.nasa.gov/data/TRMM_L3/TRMM_3B42_Daily.7">http://disc2.gesdisc.eosdis.nasa.gov/data/TRMM_L3/TRMM_3B42_Daily.7</a>
Hydrological model	W3RA	The Commonwealth Scientific and Industrial Research Organisation (CSIRO)	<a href="http://www.wenfo.org/wald/data-software/">http://www.wenfo.org/wald/data-software/</a>
Surface water storage		Satellite-derived surface water storage in the GangesBrahmaputra River Basin	<a href="#">Papa et al. (2015)</a>
In-situ measurements	BWDB	<a href="http://www.ffwc.gov.bd/">http://www.ffwc.gov.bd/</a>	

Table 2: Statistics of groundwater errors. For each case, the RMSE average and its range ( $\pm XX$ ) at the 95% confidence interval is presented. Improvements in data assimilation results are calculated with respect to the groundwater storages from the model without implementing data assimilation.

Assimilation scenario	Correlation	RMSE (mm)	Improvement (%)	
			Correlation	RMSE (mm)
Case 1 [Removed surface storages from GRACE TWS]	0.86	35 $\pm$ 5.65	51.16	57.36
Case 2 [Added surface storages to W3RA surface water]	0.82	39 $\pm$ 5.18	48.78	52.92
Case 3 [No surface storage correction applied]	0.75	68 $\pm$ 7.72	44.02	18.25
WGHM	0.79	57 $\pm$ 5.37	46.83	30.89
Mode-free run	0.42	83 $\pm$ 9.29	–	–

Table 3: Average correlations improvements (at 95% confidence interval) between in-situ and soil moisture estimates with respect to model-free run.

<b>Filter</b>	<b>0-10 cm</b>	<b>0-20 cm</b>	<b>0-50 cm</b>
Case 1	10.42	19.27	25.25
Case 2	11.10	17.88	24.48
Case 3	5.25	8.34	12.91
WGHM	–	–	17.51
W3	–	–	15.23

Table 4: Statistics of water storage variations.

Water storage	Variation rate (mm/year)	Depletion (%)			Correlation (95% confidence interval)	
		Min	Max	Mean	Precipitation	Water level height
Surface water	-1.54	0	38	11	0.74	0.81
Groundwater	-8.73	12	41	32	0.59	0.63



Table 5: Groundwater storage correlation to precipitation, TWS, and river level height variations.

	Precipitation	GRACE TWS	River level height
Before EMD	0.57	0.73	0.63
After EMD	0.71	0.88	0.77
Improvement(%)	12	15	14